

# SUPERCUT

## ENGINEERING WORKS

An ISO/TS 16949:2009 Certified Company

### STYLE RX SELECTION CHART

Ring Number	API Groove #	Size of Flange Inches			Weight lbs.	
		720-960 2000lbs.	2900lbs.	3000lbs.		5000lbs.
RX 20	R20	1 1/2		1 1/2	0.53	
RX 23	R23	2			1.15	
RX 24	R24			2	1.33	
RX 25	R25				.80	
RX 26	R26	2 1/2			1.42	
RX 27	R27			2 1/2	1.50	
RX 31	R31	3		3	1.73	
RX 35	R35				1.91	
RX 37	R37	4		4	2.09	
RX 39	R39				2.27	
RX 41	R41	5		5	2.54	
RX 44	R44				2.72	
RX 45	R45	6		6	2.96	
RX 46	R46				3.66	
RX 47	R47				8*	8.56
RX 49	R 49	8		8	3.79	
RX 50	R 50				8	5.36
RX 53	R 53	10		10	4.56	
RX 54	R 54				10	6.45
RX 57	R 57	12		12	5.36	
RX 63	R 63				14	26.40
RX 65	R 65	16				6.63
RX 66	R 66			16		9.39
RX 69	R 69	18				7.52
RX 70	R 70			18		20.14
RX 73	R 73	20				11.63
RX 74	R 74			20		22.10
RX 82	R 82		1			0.79
RX 84	R 84		1 1/2			0.88
RX 85	R 85		2			0.88
RX 86	R 86		2 1/2			1.79
RX 87	R 87		3			1.98
RX 88	R 88		4			3.22
RX 89	R 89		3 1/2			2.98
RX 90	R 90		5			6.82
RX 91	R 91		10			17.10
RX 99	R 99	8*		8*		3.31
RX 201	R 201				1 3/8	0.14
RX 205	R 205				2 13/16	0.16
RX210	R 210				2 9/16	0.77
RX 215	R 215				4 1/16	1.76